



Ref. Certif. No.

JPTUV-065696

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST
CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE
CERTIFICATS D'ESSAIS DES EQUIPEMENTS
ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE

CERTIFICAT D'ESSAI OC

Product
Produit

Li-ion Battery

Name and address of the applicant
Nom et adresse du demandeur

Shenzhen Glida Electronics Co., Ltd.
5/F, Building C, Huanyu Industrial
Park, Xuezi Road., Bao'an District, Shenzhen 518100, P.R. China

Name and address of the manufacturer
Nom et adresse du fabricant

Shenzhen Glida Electronics Co., Ltd.
5/F, Building C, Huanyu Industrial
Park, Xuezi Road., Bao'an District, Shenzhen 518100, P.R. China

Name and address of the factory
Nom et adresse de l'usine

Shenzhen Glida Electronics Co., Ltd.
5/F, Building C, Huanyu Industrial
Park, Xuezi Road., Bao'an District, Shenzhen 518100, P.R. China

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

DC 14.4V, 6800mAh, 97.92Wh

Trademark (if any)
Marque de fabrique (si elle existe)

Glida

Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeur

N/A

Model / Type Ref.
Ref. de type

18650 Battery pack

Additional information (if necessary may also be
reported on page 2)
Les informations complémentaires (si nécessaire,
peuvent être indiqués sur la 2^{ème} page)

A sample of the product was tested and found
to be in conformity with
Un échantillon de ce produit a été essayé et a été
considéré conforme à la

IEC 62133:2012
National differences see test report

As shown in the Test Report Ref. No. which forms part
of this Certificate
Comme indiqué dans le Rapport d'essais numéro de
référence qui constitue partie de ce Certificat

17050973 001

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme National de Certification



TÜVRheinland®

TÜV Rheinland Japan Ltd.
Global Technology Assessment Center
4-25-2 Kita-Yamata, Tsuzuki-ku
Yokohama 224-0021 Japan
Phone + 81 45 914-3888
Fax + 81 45 914-3354
Mail: info@jpn.tuv.com
Web: www.tuv.com

Date: 27.08.2015

Signature:

Dipl.-Ing. (FH) C. Padel



Test Report issued under the responsibility of:



**TEST REPORT
IEC 62133**

Secondary cells and batteries containing alkaline or other non-acid electrolytes – Safety requirements for portable sealed secondary cells, and for batteries made from them, for use in portable applications

Report Number: 17050973 001

Date of issue: 2015-08-27

Total number of pages: 25 pages

Applicant's name.....: Shenzhen Glida Electronics Co., Ltd.

Address: 5/F, Building C, Huanyu Industrial Park, Xuezi Road, Bao'an District, Shenzhen 518100, P.R. China

Test specification:

Standard: IEC 62133: 2012 (Second Edition)

Test procedure: CB Scheme

Non-standard test method.....: N/A

Test Report Form No.....: IEC62133B

Test Report Form(s) Originator: UL(Demko)

Master TRF: Dated 2013-03

Copyright © 2013 Worldwide System for Conformity Testing and Certification of Electrotechnical Equipment and Components (IECEE), Geneva, Switzerland. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

If this Test Report Form is used by non-IECEE members, the IECEE/IEC logo and the reference to the CB Scheme procedure shall be removed.

This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by an NCB in accordance with IECEE 02.

Test item description: Li-ion Battery

Trade Mark:



Manufacturer.....: Same as applicant

Model/Type reference: 18650 Battery pack

Ratings: DC 14.4V, 6800mAh, 97.92Wh

Testing procedure and testing location:		
<input checked="" type="checkbox"/>	CB Testing Laboratory:	Guangzhou MCM Certification & Testing Co., Ltd.
Testing location/ address		1 F No.13, Zhong San Section, Shi Guang Road, Zhong Cun Street, Panyu District, Guangzhou, Guangdong CHINA
<input type="checkbox"/>	Associated CB Testing Laboratory:	
Testing location/ address		
Tested by (name + signature).....:		Huang Tiansheng <i>Huang Tiansheng</i>
Approved by (name + signature)		Liang Hongcheng <i>Liang Hongcheng</i>
<input type="checkbox"/>	Testing procedure: TMP	
Testing location/ address		
Tested by (name + signature).....:		
Approved by (name + signature)		
<input type="checkbox"/>	Testing procedure: WMT	
Testing location/ address		
Tested by (name + signature).....:		
Witnessed by (name + signature)		
Approved by (name + signature)		
<input type="checkbox"/>	Testing procedure: SMT	
Testing location/ address		
Tested by (name + signature).....:		
Approved by (name + signature)		
Supervised by (name + signature)....:		

List of Attachments (including a total number of pages in each attachment): Attachment 1: Photo documents (4 pages)	
Summary of testing:	
Tests performed (name of test and test clause): cl.5.6.2 Design recommendation(Lithium system); cl.8.1 Charging procedure for test purposes (for Cell and Pack); cl.8.2.1 Continuous charging at constant voltage (Cells); cl.8.2.2 Moulded case stress at high ambient temperature (Battery); cl.8.3.1 External short circuit (Cell); cl.8.3.3 Free fall (for Cell and Pack); cl.8.3.4 Thermal abuse (Cells); cl.8.3.5 Crush (Cells); cl.8.3.6 Over-charging of battery; cl.8.3.7 Forced discharge (Cells); cl.8.3.8 Transport tests (Cells); Tests are made with the number of cells and batteries specified in IEC 62133: 2012 (Second Edition) Table 2.	Testing location: Guangzhou MCM Certification & Testing Co., Ltd. 1 F No.13, Zhong San Section, Shi Guang Road, Zhong Cun Street, Panyu District, Guangzhou, Guangdong CHINA
Summary of compliance with National Differences: BE, BY, CN, DE, DK, FI, GB, HU, NL, NO, SE, SG. BE=Belgium, BY=Belarus, CN=China, DE=Germany, DK=Denmark, FI=Finland, GB=United Kingdom, HU=Hungary, NL=The Netherlands, NO=Norway, SE=Sweden, SG=Singapore. <input checked="" type="checkbox"/> The product fulfils the requirements of <u>EN 62133: 2013</u>	

Copy of marking plate:

The artwork below may be only a draft. The use of certification marks on a product must be authorized by the respective NCBs that own these marks.



Test item particulars.....:	
Classification of installation and use.....:	To be defined in final product
Supply connection.....:	DC Connector
Recommend charging method declared by the manufacturer	Charging the battery with 3240mA constant current until 16.8V, then constant voltage until charging current reduces to 136mA at ambient 20°C±5°C.
Discharge current (0,2 I_t A)	1360mA
Specified final voltage	10.0V
Chemistry	<input type="checkbox"/> nickel systems <input checked="" type="checkbox"/> lithium systems
Recommend of charging limit for lithium system	
Upper limit charging voltage per cell.....:	4.25V
Maximum charging current	3400mA
Charging temperature upper limit	40°C
Charging temperature lower limit.....:	0°C
Polymer cell electrolyte type	<input type="checkbox"/> gel polymer <input type="checkbox"/> solid polymer <input checked="" type="checkbox"/> N/A
Possible test case verdicts:	
- test case does not apply to the test object.....:	N/A
- test object does meet the requirement.....:	P (Pass)
- test object does not meet the requirement.....:	F (Fail)
Testing.....:	
Date of receipt of test item	2015-07-30
Date (s) of performance of tests	2015-07-30 to 2015-08-19
General remarks:	
<p>The test results presented in this report relate only to the object tested. This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory. "(See Enclosure #)" refers to additional information appended to the report. "(See appended table)" refers to a table appended to the report. Throughout this report a <input type="checkbox"/> comma / <input checked="" type="checkbox"/> point is used as the decimal separator.</p>	
Manufacturer's Declaration per sub-clause 4.2.5 of IEC62 02:	
The application for obtaining a CB Test Certificate includes more than one factory location and a declaration from the Manufacturer stating that the sample(s) submitted for evaluation is (are) representative of the products from each factory has been provided :	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> Not applicable
When differences exist; they shall be identified in the General product information section.	
Name and address of factory (ies)	Same as applicant

General product information:

This battery is constructed with eight lithium-ion cells (4S2P) and has overcharge, over-discharge, over current and short-circuits proof circuit.

The main features of the cell in the battery pack are shown as below (clause 8.1.1):

Model	Nominal capacity	Nominal voltage	Nominal Charge Current	Nominal Discharge Current	Maximum Charge Current	Maximum Discharge Current	Maximum Charge Voltage	Cut-off Voltage
NCR18650B	3400mAh	3.6V	1620mA	650mA	2380mA	4870mA	4.23V	2.5V

The main features of the cell in the battery pack are shown as below (clause 8.1.2):

Model	Upper limit charge voltage	Taper-off current	Lower charge temperature	Upper charge temperature
NCR18650B	4.25V	170mA	0°C	40°C


The main features of the battery pack are shown as below (clause 8.1.1):

Model	Nominal capacity	Nominal voltage	Nominal Charge Current	Nominal Discharge Current	Maximum Charge Current	Maximum Discharge Current	Maximum Charge Voltage	Cut-off Voltage
18650 Battery pack	6800mAh	14.4V	3240mA	3000mA	3400A	8000A	16.8V	10V


The main features of the battery pack are shown as below (clause 8.1.2):

Model	Upper limit charge voltage	Taper-off current	Lower charge temperature	Upper charge temperature
18650 Battery pack	17.0V	340mA	0°C	40°C

Construction Unit(mm):



Circuit diagram:



IEC 62133: 2012			
Clause	Requirement + Test	Result - Remark	Verdict
4	Parameter measurement tolerances		P
	Parameter measurement tolerances		P
5	General safety considerations		P
5.1	General		P
5.2	Insulation and wiring		P
	The insulation resistance between the positive terminal and externally exposed metal surfaces of the battery (excluding electrical contact surfaces) is not less than 5 MΩ	No metal case exists.	N/A
	Insulation resistance (MΩ)..... :		—
	Internal wiring and insulation are sufficient to withstand maximum anticipated current, voltage and temperature requirements		P
	Orientation of wiring maintains adequate creepage and clearance distances between conductors		P
	Mechanical integrity of internal connections accommodates reasonably foreseeable misuse		P
5.3	Venting		P
	Battery cases and cells incorporate a pressure relief mechanism or are constructed so that they relieve excessive internal pressure at a value and rate that will preclude rupture, explosion and self-ignition	Explosion-proof safety valve for venting exists.	P
	Encapsulation used to support cells within an outer casing does not cause the battery to overheat during normal operation nor inhibit pressure relief		N/A
5.4	Temperature/voltage/current management		P
	Batteries are designed such that abnormal temperature rise conditions are prevented	Overcharge, overdischarge, over current and short-circuit proof circuit used in this battery. See tests of clause 8.	P
	Batteries are designed to be within temperature, voltage and current limits specified by the cell manufacturer	See above.	P
	Batteries are provided with specifications and charging instructions for equipment manufacturers so that associated chargers are designed to maintain charging within the temperature, voltage and current limits specified	The charging limits specified in the user manual.	P
5.5	Terminal contacts		P

IEC 62133: 2012			
Clause	Requirement + Test	Result - Remark	Verdict
	Terminals have a clear polarity marking on the external surface of the battery	Special designed connector used. Also the connector construction designed wrong polarity insert prevented.	P
	The size and shape of the terminal contacts ensure that they can carry the maximum anticipated current	DC connector contacts complied with the requirements.	P
	External terminal contact surfaces are formed from conductive materials with good mechanical strength and corrosion resistance		P
	Terminal contacts are arranged to minimize the risk of short circuits		P
5.6	Assembly of cells into batteries		P
5.6.1	If there is more than one battery housed in a single battery case, cells used in the assembly of each battery have closely matched capacities, be of the same design, be of the same chemistry and be from the same manufacturer	Two cells in parallel, four cellblocks in series (4S2P).	P
	Each battery has an independent control and protection		N/A
	Manufacturers of cells make recommendations about current, voltage and temperature limits so that the battery manufacturer/designer may ensure proper design and assembly		P
	Batteries that are designed for the selective discharge of a portion of their series connected cells incorporate separate circuitry to prevent the cell reversal caused by uneven discharges		N/A
	Protective circuit components are added as appropriate and consideration given to the end-device application		P
	When testing a battery, the manufacturer of the battery provides a test report confirming the compliance according to this standard		N/A
5.6.2	Design recommendation for lithium systems only		P
	For the battery consisting of a single cell or a single cellblock: - Charging voltage of the cell does not exceed the upper limit of the charging voltage specified in Clause 8.1.2, Table 4; or		N/A
	- Charging voltage of the cell does not exceed the different upper limit of the charging voltage determined through Clause 8.1.2, NOTE 1.		N/A

IEC 62133: 2012			
Clause	Requirement + Test	Result - Remark	Verdict
	For the battery consisting of series-connected plural single cells or series-connected plural cellblocks: - The voltages of any one of the single cells or single cellblocks does not exceed the upper limit of the charging voltage, specified in Clause 8.1.2, Table 4, by monitoring the voltage of every single cell or the single cellblocks; or	Two cells in parallel, four cellblocks in series (4S2P). Max. charging voltage of each cell is 4.23V, not exceed 4.25V specified in Clause 8.1.2, Table 4.	P
	- The voltages of any one of the single cells or single cellblocks does not exceed the different upper limit of the charging voltage, determined through Clause 8.1.2, NOTE 1, by monitoring the voltage of every single cell or the single cellblocks		N/A
	For the battery consisting of series-connected plural single cells or series-connected plural cellblocks: - Charging is stopped when the upper limit of the charging voltage, specified in Clause 8.1.2, Table 4, is exceeded for any one of the single cells or single cellblocks by measuring the voltage of every single cell or the single cellblocks; or		N/A
	- Charging is stopped when the upper limit of the different charging voltage, determined through Clause 8.1.2, NOTE 1, is exceeded for any one of the single cells or single cellblocks by measuring the voltage of every single cell or the single cellblocks		N/A
5.7	Quality plan		P
	The manufacturer prepares and implements a quality plan that defines procedures for the inspection of materials, components, cells and batteries and which covers the whole process of producing each type of cell or battery	Complied. ISO 9001: 2008 certificate provided.	P
6	Type test conditions		P
	Tests were made with the number of cells or batteries specified in Table 1 for nickel-cadmium and nickel-metal hydride systems and Table 2 for lithium systems, using cells or batteries that are not more than six months old	Complied. Lithium system.	P
	Unless noted otherwise in the test methods, testing was conducted in an ambient of $20 \pm 5^{\circ}\text{C}$.	Tests are carried out at $20 \pm 5^{\circ}\text{C}$.	P
7	Specific requirements and tests (nickel systems)		N/A
7.1	Charging procedure for test purposes	Lithium system.	N/A
7.2	Intended use		N/A
7.2.1	Continuous low-rate charging (cells)		N/A
	Results: No fire. No explosion		N/A

IEC 62133: 2012			
Clause	Requirement + Test	Result - Remark	Verdict
7.2.2	Vibration		N/A
	Results: No fire. No explosion. No leakage	(See Table 7.2.2)	N/A
7.2.3	Moulded case stress at high ambient temperature		N/A
	Oven temperature (°C)		—
	Results: No physical distortion of the battery casing resulting in exposure if internal components		N/A
7.2.4	Temperature cycling		N/A
	Results: No fire. No explosion. No leakage.		N/A
7.3	Reasonably foreseeable misuse		N/A
7.3.1	Incorrect installation cell		N/A
	The test was carried out using: - Four fully charged cells of the same brand, type, size and age connected in series, with one of them reversed; or		N/A
	- A stabilized dc power supply.		N/A
	Results: No fire. No explosion	(See Table 7.3.1)	N/A
7.3.2	External short circuit		N/A
	The cells or batteries were tested until one of the following occurred: - 24 hours elapsed; or		N/A
	- The case temperature declined by 20% of the maximum temperature rise		N/A
	Results: No fire. No explosion	(See Table 7.3.2)	N/A
7.3.3	Free fall		N/A
	Results: No fire. No explosion.		N/A
7.3.4	Mechanical shock (crash hazard)		N/A
	Results: No fire. No explosion. No leakage.		N/A
7.3.5	Thermal abuse		N/A
	Oven temperature (°C)		—
	Results: No fire. No explosion.		N/A
7.3.6	Crushing of cells		N/A
	The crushing force was released upon: - The maximum force of 13 kN ± 1 kN has been applied; or		N/A
	- An abrupt voltage drop of one-third of the original voltage has been obtained		N/A

IEC 62133: 2012			
Clause	Requirement + Test	Result - Remark	Verdict
	The cell is prismatic type and a second set of samples was tested, rotated 90° around longitudinal axis compared to the first set		N/A
	Results: No fire. No explosion	(See Table 7.3.6)	N/A
7.3.7	Low pressure		N/A
	Chamber pressure (kPa)		—
	Results: No fire. No explosion. No leakage.		N/A
7.3.8	Overcharge		N/A
	Results: No fire. No explosion	(See Table 7.3.8)	N/A
7.3.9	Forced discharge		N/A
	Results: No fire. No explosion	(See Table 7.3.9)	N/A
8	Specific requirements and tests (lithium systems)		P
8.1	Charging procedures for test purposes		P
8.1.1	First procedure: This charging procedure applied to tests other than those specified in 8.1.2		P
8.1.2	Second procedure: This charging procedure applied to the tests of 8.3.1, 8.3.2, 8.3.4, 8.3.5, and 8.3.9		P
	If a cell's specified upper and/or lower charging temperature exceeds values for the upper and/or lower limit test temperatures of Table 4, the cells were charged at the specified values plus 5 °C for the upper limit and minus 5 °C for the lower limit	45°C used for upper limit test temperature; -5°C used for lower limit test temperature.	P
	A valid rationale was provided to ensure the safety of the cell (see Figure A.1)		P
	For a different upper limit charging voltage (i.e. other than for lithium cobalt oxide systems at 4.25 V), the applied upper limit charging voltage and upper limit charging temperatures were adjusted accordingly	Lithium cobalt oxide system only.	N/A
	A valid rationale was provided to ensure the safety of the cell (see Figure A.1)	The upper limit charging voltage: 4.25V	N/A
8.2	Intended use		P
8.2.1	Continuous charging at constant voltage (cells)	Tested complied.	P
	Results: No fire. No explosion	(See Table 8.2.1)	P
8.2.2	Moulded case stress at high ambient temperature (battery)		P
	Oven temperature (°C)	70°C	—

IEC 62133: 2012			
Clause	Requirement + Test	Result - Remark	Verdict
	Results: No physical distortion of the battery casing resulting in exposure if internal components		P
8.3	Reasonably foreseeable misuse		P
8.3.1	External short circuit (cell)		P
	The cells were tested until one of the following occurred: - 24 hours elapsed; or		N/A
	- The case temperature declined by 20% of the maximum temperature rise	Tested complied.	P
	Results: No fire. No explosion	(See Table 8.3.1)	P
8.3.2	External short circuit (battery)		P
	The cells were tested until one of the following occurred: - 24 hours elapsed; or	Tested complied.	P
	- The case temperature declined by 20% of the maximum temperature rise		N/A
	In case of rapid decline in short circuit current, the battery pack remained on test for an additional one hour after the current reached a low end steady state condition		N/A
	Results: No fire. No explosion	(See Table 8.3.2)	P
8.3.3	Free fall		P
	Results: No fire. No explosion.	No fire. No explosion.	P
8.3.4	Thermal abuse (cells)		P
	The cells were held at 130°C ± 2°C for: - 10 minutes; or	Tested complied.	P
	- 30 minutes for large cells (gross mass of more than 500 g as defined in IEC 62281)		N/A
	Oven temperature (°C)	130°C	P
	Gross mass of cell (g)	Small cell.	P
	Results: No fire. No explosion.	No fire. No explosion.	P
8.3.5	Crush (cells)		P
	The crushing force was released upon: - The maximum force of 13 kN ± 1 kN has been applied; or	Tested complied.	P
	- An abrupt voltage drop of one-third of the original voltage has been obtained; or		N/A
	- 10% of deformation has occurred compared to the initial dimension		N/A

IEC 62133: 2012			
Clause	Requirement + Test	Result - Remark	Verdict
	Results: No fire. No explosion	(See Table 8.3.5)	P
8.3.6	Over-charging of battery	Tested complied.	P
	Test was continued until the temperature of the outer casing: - Reached steady state conditions (less than 10°C change in 30-minute period); or		N/A
	- Returned to ambient		P
	Results: No fire. No explosion	(See Table 8.3.6)	P
8.3.7	Forced discharge (cells)		P
	Results: No fire. No explosion	(See Table 8.3.7)	P
8.3.8	Transport tests		P
	Manufacturer's documentation provided to show compliance with UN Recommendations on Transport of Dangerous Goods	T-1, T-2, T-3 and T-4 tested complied. No leakage, no venting, no short-circuit, no rupture, no explosion and no fire. T-5, See Table 8.3.8. T-6 tested also complied, refer to Clause 8.3.5.	P
8.3.9	Design evaluation – Forced internal short circuit (cells)	The applicant declares that this cell isn't to be sold in France, Japan, Republic of Korea and Switzerland.	N/A
	The cells complied with national requirement for		—
	The pressing was stopped upon: - A voltage drop of 50 mV has been detected; or		N/A
	- The pressing force of 800 N (cylindrical cells) or 400 N (prismatic cells) has been reached		N/A
	Results: No fire		N/A
9	Information for safety		P
	The manufacturer of secondary cells ensures that information is provided about current, voltage and temperature limits of their products.	Information for safety mentioned in manufacturer's specifications.	P
	The manufacturer of batteries ensures that equipment manufacturers and, in the case of direct sales, end-users are provided with information to minimize and mitigate hazards.	Information for safety mentioned in manufacturer's specifications.	P
	Systems analyses performed by device manufacturers to ensure that a particular battery design prevents hazards from occurring during use of a product		N/A

IEC 62133: 2012			
Clause	Requirement + Test	Result - Remark	Verdict

	As appropriate, information relating to hazard avoidance resulting from a system analysis is provided to the end user.....:		N/A
--	---	--	-----

10	Marking		P
10.1	Cell marking		N/A
	Cells marked as specified in the applicable cell standards: IEC 61951-1, IEC 61951-2 or IEC 61960.	The final product is battery.	N/A
10.2	Battery marking		P
	Batteries marked in accordance with the requirements for the cells from which they are assembled.	The battery is marked in accordance with IEC 61960, also see page 4.	P
	Batteries marked with an appropriate caution statement.		N/A
10.3	Other information		P
	Storage and disposal instructions marked on or supplied with the battery.	Information for disposal instructions mentioned in manufacturer's specifications.	P
	Recommended charging instructions marked on or supplied with the battery.	Information for recommended charging instructions mentioned in manufacturer's specifications.	P

11	Packaging		P
	The materials and packaging design are chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of environmental contaminants.		P

Annex A	Charging range of secondary lithium ion cells for safe use		P
A.1	General		P
A.2	Safety of lithium-ion secondary battery	Complied.	P
A.3	Consideration on charging voltage	Complied.	P
A.3.1	General	Max.Charging voltage is 4.23V.	P
A.3.2	Upper limit charging voltage	4.25V	P
A.3.2.1	General		P
A.3.2.2	Explanation of safety viewpoint		N/A
A.3.2.3	Safety requirements, when different upper limit charging voltage is applied	4.25V applied.	N/A

IEC 62133: 2012			
Clause	Requirement + Test	Result - Remark	Verdict
A.4	Consideration of temperature and charging current		P
A.4.1	General		P
A.4.2	Recommended temperature range	See A.4.2.2.	P
A.4.2.1	General		P
A.4.2.2	Safety consideration when a different recommended temperature range is applied	Charging temperature declared by client is: 0-40°C	P
A.4.3	High temperature range		N/A
A.4.3.1	General		N/A
A.4.3.2	Explanation of safety viewpoint		N/A
A.4.3.3	Safety considerations when specifying charging conditions in high temperature range		N/A
A.4.3.4	Safety consideration when specifying new upper limit in high temperature range	45°C applied.	N/A
A.4.4	Low temperature range	Charging low temperature declared by client is: 0°C.	P
A.4.4.1	General		P
A.4.4.2	Explanation of safety viewpoint		P
A.4.4.3	Safety considerations, when specifying charging conditions in low temperature range		P
A.4.4.4	Safety considerations when specifying a new lower limit in the low temperature range	-5°C applied.	P
A.4.5	Scope of the application of charging current		P
A.5	Sample preparation		N/A
A.5.1	General		N/A
A.5.2	Insertion procedure for nickel particle to generate internal short		N/A
	The insertion procedure carried out at 20°C±5°C and under -25 °C of dew point		N/A
A.5.3	Disassembly of charged cell		N/A
A.5.4	Shape of nickel particle		N/A
A.5.5	Insertion of nickel particle to cylindrical cell		N/A
A.5.5.1	Insertion of nickel particle to winding core		N/A
A.5.5.2	Mark the position of nickel particle on the both end of winding core of the separator		N/A
A.5.6	Insertion of nickel particle to prismatic cell		N/A

TABLE: Critical components information					P
Object/part no.	Manufacturer/ trademark	Type/model	Technical data	Standard	Mark(s) of conformity ¹⁾
Enclosure	TAIXINDADINA ZI	110X0.11mm	PC, 105°C	--	Test with appliance
Lead wire	Interchangeable	Interchangeable	24AWG, 80°C	--	--
Lead wire	Interchangeable	Interchangeable	28AWG, 80°C	--	--
PCB	Interchangeable	Interchangeable	V-1or better, 130°C	--	--
IC (U1)	TI	BQ20Z65	Fully Integrated 2- Series, 3-Series, and 4-Series Li-Ion or Li-Polymer Cell Battery Pack Manager and Protection	--	Test with appliance
IC (U2)	TI	BQ29412DCTR	Supply Voltage Range: 0.3 V to 28V	--	Test with appliance
IC (U3)	TI	TLC59208F	Supply Voltage : 3.3 V to 5V	--	Test with appliance
IC (U4)	TI	TLV70433	Vmax.=24V	--	Test with appliance
MOSFET (Q7)	aosmd	AO4407	VDS=30V, ID= 12A	--	Test with appliance
MOSFET (Q1, Q6, Q8)	Vishay	SI 2318	VDS=40V, ID= 3A	--	Test with appliance
MOSFET (Q2, Q3, Q4, Q5)	aosmd	AO4430	VDS=:30V, ID= 18A	--	Test with appliance
Fuse	NEC	DX60	32V, 12A	--	--
Cell	PANASONIC CORPORATION , PANASONIC CORPORATION OF NORTH AMERICA	NCR18650B	DC 3.6V, 3400mAh	UL1642 IEC 62133: 2012	UL MH12210 Tested with appliance
Supplementary information: ¹⁾ Provided evidence ensures the agreed level of compliance.					

7.2.1	TABLE: Continuous low rate charge (cells)					N/A
Model	Recommended charging method, (CC, CV, or CC/CV)	Recommended charging voltage V_c , (Vdc)	Recommended charging current I_{rec} , (A)	OCV at start of test, (Vdc)	Results	
Supplementary information: <ul style="list-style-type: none"> - No fire or explosion - No leakage - Leakage - Fire - Explosion - Bulge - Others (please explain) 						

7.2.2	TABLE: Vibration		N/A
Model	OCV at start of test, (Vdc)	Results	
Supplementary information: <ul style="list-style-type: none"> - No fire or explosion - No leakage - Leakage - Fire - Explosion - Bulge - Others (please explain) 			

7.3.1	TABLE: Incorrect installation (cells)		N/A
Model		OCV of reversed cell, (Vdc)	Results
Supplementary information: - No fire or explosion - No leakage - Leakage - Fire - Explosion - Bulge - Others (please explain)			

7.3.2	TABLE: External short circuit				N/A
Model	Ambient (at 20°C ± 5°C or 55°C ± 5°C)	OCV at start of test, (Vdc)	Resistance of circuit, (Ω)	Maximum case temperature rise ΔT, (°C)	Results
Supplementary information: - No fire or explosion - No leakage - Leakage - Fire - Explosion - Bulge - Others (please explain)					

7.3.6	TABLE: Crush			N/A
Model	OCV at start of test, (Vdc)	OCV at removal of crushing force, (Vdc)	Results	
Supplementary information: - No fire or explosion - No leakage - Leakage - Fire - Explosion - Bulge - Others (please explain)				

7.3.8	TABLE: Overcharge			N/A
Model	OCV prior to charging, (Vdc)	Maximum charge current, (A)	Time for charging, (hours)	Results
Supplementary information: - No fire or explosion - No leakage - Leakage - Fire - Explosion - Bulge - Others (please explain)				

7.3.9	TABLE: Forced discharge (cells)				N/A
Model	OCV before application of reverse charge, (Vdc)	Measured reverse charge I_t , (A)	Time for reversed charge, (minutes)	Results	
Supplementary information: - No fire or explosion - No leakage - Leakage - Fire - Explosion - Bulge - Others (please explain)					

8.2.1	TABLE: Continuous charging at constant voltage (cells)				P
Model	Recommended charging voltage V _c , (Vdc)	Recommended charging current I _{rec} , (A)	OCV at start of test, (Vdc)	Results	
Cell #1	4.20	1.62	4.18	P	
Cell #2	4.20	1.62	4.18	P	
Cell #3	4.20	1.62	4.19	P	
Cell #4	4.20	1.62	4.18	P	
Cell #5	4.20	1.62	4.18	P	
Supplementary information: - No fire, no explosion, no leakage					

8.3.1	TABLE: External short circuit (cell)					P
Model	Ambient, (°C)	OCV at start of test, (Vdc)	Resistance of circuit, (mΩ)	Maximum case temperature rise ΔT , (°C)	Results	
Samples charged at charging temperature upper limit (45°C)						
Cell #1	21.8	4.15	80.2	72.2	P	
Cell #2	21.8	4.15	81.4	73.8	P	
Cell #3	21.8	4.15	84.3	71.6	P	
Cell #4	21.8	4.15	79.8	65.8	P	
Cell #5	21.8	4.15	78.7	73.1	P	
Samples charged at charging temperature lower limit (-5°C)						
Cell #6	22.0	4.10	75.8	71.7	P	
Cell #7	22.0	4.10	76.2	72.0	P	
Cell #8	22.0	4.10	80.4	66.9	P	
Cell #9	22.0	4.10	81.2	74.6	P	
Cell #10	22.0	4.10	83.2	72.4	P	
Supplementary information:						
- No fire, no explosion						

8.3.2	TABLE: External short circuit (battery)					P
Model	Ambient, (°C)	OCV at start of test, (Vdc)	Resistance of circuit, (mΩ)	Maximum case temperature rise ΔT , (°C)	Results	
Samples charged at charging temperature upper limit (45°C)						
Battery #1	53.4	16.10	80.2	54.9	P	
Battery #2	53.4	16.17	81.4	55.6	P	
Battery #3	53.4	16.11	84.3	55.7	P	
Battery #4	53.4	15.99	79.8	55.3	P	
Battery #5	53.4	15.97	78.7	57.3	P	
Samples charged at charging temperature lower limit (-5°C)						
Battery #6	54.9	15.39	75.8	56.1	P	
Battery #7	54.9	15.29	76.2	55.9	P	
Battery #8	54.9	15.58	80.4	55.8	P	
Battery #9	54.9	15.67	81.2	57.3	P	
Battery #10	54.9	15.44	83.2	56.2	P	
Supplementary information:						
- No fire, no explosion						

8.3.5	TABLE: Crush					P
Model	OCV at start of test, (Vdc)	OCV at removal of crushing force, (Vdc)	Width/ diameter of cell before crush, (mm)	Required deformation for crush, (mm)	Results	
Samples charged at charging temperature upper limit (45°C)						
Cell #1	4.15	4.15	--	--	P	
Cell #2	4.14	4.14	--	--	P	
Cell #3	4.15	4.15	--	--	P	
Cell #4	4.14	4.14	--	--	P	
Cell #5	4.15	4.15	--	--	P	
Note: A 13kN force applied at the wide side of prismatic cells. No voltage abrupt drop occurred. Supplementary information: - No fire, no explosion.						

8.3.6	TABLE: Over-charging of battery				P
Constant charging current (A).....:			13.6		—
Supply voltage (Vdc).....:			20.0		—
Model	OCV before charging, (Vdc)	Resistance of circuit, (mΩ)	Maximum outer casing temperature, (°C)	Results	
Battery #1	12.36	12.1	19.5	P	
Battery #2	12.35	10.8	20.1	P	
Battery #3	12.41	10.2	20.7	P	
Battery #4	12.29	11.7	21.1	P	
Battery #5	12.18	12.5	22.0	P	
Supplementary information: - No fire, no explosion					

8.3.7	TABLE: Forced discharge (cells)				P
Model	OCV before application of reverse charge, (Vdc)	Measured Reverse charge I_r , (A)	Time for reversed charge, (minutes)	Results	
Cell #1	3.08	3.4	90	P	
Cell #2	3.09	3.4	90	P	
Cell #3	3.08	3.4	90	P	
Cell #4	3.08	3.4	90	P	
Cell #5	3.08	3.4	90	P	
Supplementary information: - No fire, no explosion					

8.3.8 T-5	TABLE: External short circuit (cell)					P
Model	Ambient, (°C)	OCV at start of test, (Vdc)	Resistance of circuit, (mΩ)	Maximum case temperature rise ΔT_r , (°C)	Results	
Cell #1	55.7	4.14	80.2	80.1	P	
Cell #2	55.7	4.13	81.4	79.2	P	
Cell #3	55.7	4.13	84.3	79.5	P	
Cell #4	55.7	4.12	79.8	76.0	P	
Cell #5	55.7	4.14	78.7	78.1	P	
Cell #6	56.3	4.15	75.8	76.1	P	
Cell #7	56.3	4.15	76.2	82.4	P	
Cell #8	56.3	4.14	80.4	75.0	P	
Cell #9	56.3	4.13	81.2	77.9	P	
Cell #10	56.3	4.12	83.2	79.8	P	
Supplementary information: The external short-circuit test of 10 pcs samples performed after the test of Altitude, Thermal cycling, Vibration and Shock in sequence. - No excessive temperature rise, no rupture, no explosion and no fire.						

8.3.9	TABLE: Forced internal short circuit (cells)					N/A
Model	Chamber ambient, (°C)	OCV at start of test, (Vdc)	Particle location ¹⁾	Maximum applied pressure, (N)	Voltage drop, (mV)	Results

Supplementary information:

¹⁾ Identify one of the following:

1: Nickel particle inserted between positive and negative (active material) coated area.

2: Nickel particle inserted between positive aluminium foil and negative active material coated area.

- No fire

-- End of Report --

Product: Li-ion Battery

Type Designation: 18650 Battery pack



Figure 1 Front view of battery




Figure 2 Back view of battery

Product: Li-ion Battery
Type Designation: 18650 Battery pack



Figure 3 Side view of battery




Figure 4 Inside view of battery

Product: Li-ion Battery

Type Designation: 18650 Battery pack




Figure 5 PCM view of Side A




Figure 6 PCM view of Side B

Product: Li-ion Battery

Type Designation: 18650 Battery pack



Figure 7 Front view of component cell



Figure 8 Back view of component cell